



Hammer Drills

KAESER Hammer Drills
Your one-stop-shop.

Power through concrete and stone



- ✓ Impressive drilling and hammering performance
- ✓ Durable and simple design
- ✓ Exceptional versatility – perfect for use in mining, construction, quarrying and industrial applications
- ✓ From model BH11 available with power blowing system for blowing out of the drill hole

Technical specifications

	Model	Blow frequency	Air consumption *)	Chuck – Shank		Weight	Impact force	Weighted sum acceleration value **)
		per min	m ³ /min			kg	Joules	m/s ²
Grip	BH 8	3660	0.5	S 19 x 82.5	a)	8.6	8.5	15.4
	BH 8	3660	0.5	S 22 x 82.5	a)	8.6	8.5	15.4
	BH 11	2910	1.1	S 22 x 108	b)	15.5	19.0	22.0
T-grip	BH 16	2400	1.6	S 22 x 108	b)	18.9	30.0	19.0
	BH 21	2740	2.1	S 22 x 108	b)	24.4	40.0	17.7

Vibration-damped

T-grip	BH 16 V	2440	1.6	S 22 x 108	b)	22.9	30.0	10.6
--------	---------	------	-----	------------	----	------	------	------

*) At 5 bar **) As per ISO28927-10, measured at 5 bar a) = Retaining spring b) = Retaining catch
 Appropriate bits are separately available: Monoblock bit, cone drill rod, core bit

Hose lubricator (1.4I):

Recommended accessory for compressors without tool lubricators, or for compressors with integrated tool lubricator if the distance to the tool exceeds 20m, or if there is a height difference to the tool.



KAESER KOMPRESSOREN SE

P.O. Box 2143 – 96410 Coburg – GERMANY – Tel +49 9561 640-0 – Fax +49 9561 640-130
 e-mail: productinfo@kaeser.com – www.kaeser.com